

Contactless voltage detector UT12D-EU UNI-T

RTV0400160
5902270776287
LXUT12D



An excellent quality voltage detector with a wide sensitivity range, enhancing its versatility. Additional illumination allows operation in unlit and hard-to-reach areas, while visual and audible signals facilitate detector use. Compact and easy to use, ideal for storage and quick access. AC Voltage Measurement Range 12 - 1000V Frequency 50-60Hz Alarm Sound and LED indicator Flash-light White LED Automatic Power Off Yes Low Battery Notification Yes Current measurement Depending on the signal strength Non-Contact Voltage (NCV) Measurement Automatically selects from 3 frequencies (low, medium, high) NCV Intensity Indicates intensity using sound signals at different frequencies and LED colors for low, moderate, and high sensitivity Operating Temperature 0 - 40°C Storage Temperature -10 - 50°C Operating Altitude <2000m Safety Rating CE. CAT III 1000V / CAT.IV 600V Dimensions 156x20x20mm Weight about 45g

Specificație

Marca: LTC

Tip baterie: LR44

Temperatura de lucru: 0°C până la +40°C

Dimensiuni produs (mm) lung. x lăț. x înălț.: 156 x 20 x 20

Greutate brută (cu ambalaj): 45 g

Garanție: 24 mc



SCAN ME!